

NEL

PP-80G

80mm Thermal Receipt Printer



- ❖ Easy Paper Loading
- ❖ Multiple Interface Support
- ❖ Upto 300mm/s High Speed, Low noise Printing
- ❖ Supports Multi 1D Barcode and QR code Printing
- ❖ 48 or 80mm Adjustable Paper Separator for Option
- ❖ Compact Design, Fashionable Appearance
- ❖ 150Km Long Life Printer Head
- ❖ Support Wall mounting

Technical Specifications

Product Specification : PP-80G Thermal Receipt Printer	
Printer Parameters :	
Power Input : AC 100V - 240V 50-60Hz	Power Output : 24V/2.5A
Cash Drawer : DC 24V/1A	Printer Head : 150 Km
Internfaces : USB, RS-232, LAN	Cutter : Partial / Full cut
Sensors : Paper out, Cover open, Paper jammed	
OS Support : Compatible with Windows / Linux / OPoS	
Paper Width : 48mm/52mm/56mm/64mm/68mm/76mm/80mm	
Paper Thickness : 0.06 ~ 0.08 mm	Paper roll diameter : 80mm Max
Printing Method : Direct Thermal line	Printing Resolution : 203 DPI
Printing Speed	200 mm/s (U / UR)
	260 mm/s (UL / U + BT / U + WiFi)*
	300 mm/s (URL / URL+ BT / URL + WiFi)*
Decode capability : 1D : UPC-A, UPC-E, EAN-8, EAN-13, COde 128, Code 39, Code 93, Code 11, Interleaved 2 of 5, Matrix 2 of 5, Standard 2 of 5 2D : QR code, Data Matrix, PDF417, Aztec code, Maxicode, etc.	
Character Size	ANK Character Font A : 12 x 24 dots, 1.5 (W) x 3.0 (H) mm Font B : 9 x 17 dots, 1.1 (W) x 2.1 (H) mm Simplified / Traditional : 24 x 24 dots / 3.0 (W) x 3.0 (H) mm
User Defined Languages	PC437/Katakana/PC850/PC860/PC863/PC865/WesternEurope/ Greek/Hebrew/EastEurope/Iran/WPC1252/PC866/PC852/PC858/ IranII/Latvian/Arabic/PT151,1251/PC737/WPC1257/Thai/Vietnam/ PC1001/Latvian
Product Dimentions : 180 x 142 x 136 mm	Weight : 1.65 Kg
Storage temp : -20°C ~ 60°C	Working temp : 0°C ~ 45°C
Storage Humidity : 10% ~ 90%	Working Humidity : 10% ~ 80%
Certificate : CE, FCC, RoHS	

* WiFi and Bluetooth functions are optional and may replace Serial and USB ports



Image Gallery

